



Hand-Made Toe.


(Finished on machine).


62. Toe, first part.

- 
1. Stop yarn-carrier on **the** back or at **A**.
 2. Raise out of action all the needles
 3. On the front or front of centre line **BD**.
 4. Knit first part of toe on back of machine
 5. In the usual manner, see page 17, No. 36.
 6. Narrow the first part of toe down to
 7. Say six or eight needles in the centre.
 8. Stop carrier last row knit on right or at 1).
 9. Put down all needles on the left of the
 10. 6 or 8 centre needles at back or at **A**.
 11. Knit to the left, stop carrier at left or at 15.
 12. Now put down all needles remaining up,
 13. And remove heel-hooks and weights.
 14. Lift entirely out of cylinder with stitches on.
 15. All the toe needles on back of cylinder line **BD**,
 16. And place them on the inside of cylinder.
 17. Knit to the right; stop carrier at back or at **A**.
 18. Now knit second half of toe. as follows :

63. Toe, second part.

- 
1. Lift 1st needle on inside of cylinder
 2. Found on the right, and draw the yarn
 3. Through its stitch to cast off the double-loop,
 4. To make the right side stitches the same as
 5. The left side stitches which have been knit,
 6. Place the stitch on the first needle to the left.
 7. Lift out 3 needles on the left side of web.
 8. Place stitch of 3rd needle on the 4th needle.
 9. Place the remaining two needles into the grooves
 10. Formerly occupied by the 2nd and 3rd needles.
 11. Knit one row to left ; hold down work.
 12. Stop yarn-carrier at the back or at **A**.
 13. Now lift 1st needle on the left, inside of cylinder.
 14. Keeping yarn on inside. Place its stitch on the.

- 
15. First needle to right without drawing yarn through.
 16. Narrow on the right side as already done on the left.
 17. Knit one row to right, repeat lifting a needle
 18. Each row knit, always lifting the needle
 19. From inside of cylinder on same side as yarn,
 20. And narrow them on opposite side to yarn
 21. In manner described, so the needles narrowed
 22. By lifting will equal the needles narrowed
 23. By removal from the needle cylinder,
 24. Thereby keeping stitches of both sides of toe equal.
 25. Continue until all inside needles are raised.
 20. And all cylinder-needles are narrowed down
 27. To say 6 or 8 each. Then finish toe by
 28. Placing the inside cylinder-needle stitches on
 29. The 6 or 8 cylinder-needles ; break off yarn
 30. All but 10 inches, which use for closing toe.
 31. Lift out of the needle-cylinder entirely, the 1st
 32. Needle on the right and draw the yarn through
 33. The two stitches, then place stitch on next needle.
 34. Continue lifting out one needle and draw yarn
 35. Through the three stitches and place stitch on the next needle to the left,
 36. Until all the needles are lifted out of cylinder:
 37. Now draw yarn through last three stitches;
 38. Then pass the yarn through work to centre of toe.
 39. Fasten it securely and break off 3 inches from toe.
 40. The toe may be made more pointed if desired.

 *The toe can be made* in two halves, that is, each half knit and narrowed on both sides of web, two stitches from the selvedge in the manner already described for second part of toe. After both sides of toe have been narrowed down equally to (i or 8 needles, and the 6 or 8 stitches each side closed as above or with knit stitch, then the two selvedge edges are sewed together with the selvedge edge stitch, see page 29.